

| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|-----|------|-------|---------|----------------------|---|------|--------|
|-----|------|-------|---------|----------------------|---|------|--------|

ShenZhen Sintronic Technology Company Limited



SINTRONICTECH
MAKE A DIFFERENCE

Tim Wu
Sales Engineer

Address: No. 3368, Pengrunda Commercial Plaza Shenzhen City, China. 518000
 Website: <https://sintronictech.com>
 Email: tim@sintronictech.com
 Mobile: +86-15813805304
China Leading Manufacturer Access & Security System



scan this code using the WhatsApp camera to get my number





Access Control, Turnstile Gate, Security Guard
 Parking Guidance, Parking Ticketing System




Manufacturer



| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|-----|------|-------|---------|----------------------|---|------|--------|
|-----|------|-------|---------|----------------------|---|------|--------|






| | |
|----------|--|
| ③ | Metal Detector Manufacturing Department |
| | Security Guard System Price List |
| | sintronicdetector.com |



| Hand Held Metal Detector | Vehicle Inspection Mirror | Walk Through Metal Detector | X Ray Baggage Scanner |
|---|---|---|---|
|  |  |  |  |
| Page 3 | Page 4 | Page 5-9 | Page 10 |




| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|---------------------------------|---|---------|---|--|---|---------------------------------------|--------|
| Hand Held Metal Detector | | | | | | | |
| 152 | Hand Held Metal Detector (Super Scanner) | HAND 01 |  | <ol style="list-style-type: none"> 1. Detection sensitivity: detection of RMB one yuan coin, detection distance $\geq 90\text{mm}$ 2. Detection method: sound and light alarm. 3. Power supply: 9v square battery (6F22ND battery), with external charger function (Optional charger and battery) 4. Quiescent current: less than 26mA 5. Working current: sound and light less than 120mA 6. Working temperature: -5°C to 45°C 7. Dimensions: 415 * 85 * 45 mm 8. Net weight: 300g 9. Packing size: 500*260*440mm | / | More Photo ->Click | / |
| 153 | Hand Held Metal Detector (GP) | HAND 02 |  | <ol style="list-style-type: none"> 1. Detection sensitivity: detect RMB one yuan coin, the detection distance is $\geq 60\text{mm}$ 2. Alarm mode: sound and light synchronous alarm or vibration alarm. 3. Power supply: 9v square battery (6F22ND battery), external charger function (optional charger and battery) 4. Quiescent current: less than 7mA working current: sound and light less than 120mA | / | More Photo ->Click | / |
| 154 | Hand Held Metal Detector With Fashion design for exhibition | HAND 03 |  | <p>Power Supply: External charging interface or 9Vfold battery (Battery is optional accessory)</p> <ol style="list-style-type: none"> 1. Power rate: 270 milliwatts 2. Working frequency: 22 kHz 3. Working current: <50 mA 4. Working voltage: 7-9v 5. Dimensions: 390 (length) * 840 (width) * 420 (thickness) mm <p>Detect Distance: 1-12cm Alarm Indication: Audio and Vibration at the same time.</p> | / | More Photo ->Click | / |



| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|---|--|---------------------|--|--|---|---------------------------------------|--------|
| Bottom Vehicle Inspection Mirror | | | | | | | |
| 155 | Vehicle Inspection Mirror with flash light | MIRROR-01 |  | <p>1. Mirror surface: round 300*300mm acrylic high-strength shatterproof mirror surface, convex 2 times magnification effect, 1/2 the weight of ordinary glass mirror surface of the same size, with certain toughness, not easy to break, safe and durable, brightness and glass mirror surface different. Clamp-in fully enclosed round mirror with painted iron bottom can effectively prevent damage to the mirror caused by collision</p> <p>2. Pull rod: lightweight aluminum rod, telescopic range 500-1100mm</p> <p>3. Supplementary light source: 9 LED flashlight</p> <p>4. Net weight: 1.1kg Gross weight: 1.6kg</p> <p>5. Packing: 4 pcs/carton</p> <p>6. Outer box packing: 560*430*390mm</p> <p>7. Bag size: 540*340*110mm</p> | / | More Photo ->Click | / |
| 156 | Vehicle Inspection Mirror with flash light | MIRROR-INSPECTION02 |  | <p>1. Mirror surface: round 300*300mm acrylic high-strength shatterproof mirror surface, convex 2 times magnification effect, 1/2 the weight of ordinary glass mirror surface of the same size, with certain toughness, not easy to break, safe and durable, brightness and glass mirror surface different.</p> | | | / |


| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|------------------------------------|--|-------|--|--|---|--|--------|
| Walk Through Metal Detector | | | | | | | |
| Single Zone | | | | | | | |
| 157 | Economical Single Zone Walk Through Metal Detector | DF01 |  | <p>1. Detection procedure: level sensitivity adjustment, which can meet the needs of different occasions.</p> <p>2. Personnel passing rate: more than 40 person-times per minute.</p> <p>3. Power supply: 110-240V AC, 50/60Hz, power consumption: ≤ 18W.</p> <p>4. Testing standard: one yuan coin</p> <p>11. Display mode: digital tube display</p> <p>5. Working environment: -10℃ ~45℃, ≤95%RH.</p> <p>6. Channel size: 1980 (height) * 700 (width) * 300 (depth) mm</p> <p>7. Dimensions: 2220 (height) * 820 (width) * 400 (depth) mm</p> <p>8. Packing size: door panel: 2260*360*180mm (2 pieces/carton) Main box: 750*245*305mm (1pc/box).</p> <p>9. Net weight: 38kg/set Gross weight: 48kg/set</p> <p>10. Color: Available in iron gray, off-white, beige and black</p> | / | More Photo - >Click | / |

| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|---------|---|---------|--|--|---|--|--------|
| 6 Zones | | | | | | | |
| 158 | Economical 6 Zone Walk Through Metal Detector | DF06 |  | <ol style="list-style-type: none"> Detection procedure: level sensitivity adjustment, which can meet the needs of different occasions. Personnel passing rate: more than 40 person-times per minute. Power supply: 110-240V AC, 50/60Hz, power consumption: ≤ 18W. Testing standard: one yuan coin Display mode: 6-zone digital tube display Working environment: -10℃ ~45℃, ≤95%RH. Channel size: 1980 (height) * 700 (width) * 500 (depth) mm Dimensions: 2220 (height) * 820 (width) * 580 (depth) mm Packing size: door panel: 2280*570*210mm (2 pieces/carton) Main box: 770*530*260mm | | More Photo - >Click | / |
| 159 | Lighting 6 Zone Walk Through Metal Detector | DF06LED |  | <ol style="list-style-type: none"> Detection procedure: level sensitivity adjustment, which can meet the needs of different occasions. Personnel passing rate: more than 40 person-times per minute. Power supply: 110-240V AC, 50/60Hz, power consumption: ≤ 18W. Testing standard: one yuan coin Display mode: 6-zone digital tube display Working environment: -10℃ ~45℃, ≤95%RH. Channel size: 1980 (height) * 700 (width) * 500 (depth) mm Dimensions: 2220 (height) * 820 (width) * 580 (depth) mm Packing size: door panel: 2280*570*210mm (2 pieces/carton) Main box: 770*530*260mm | | More Photo - >Click | / |

| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|-----|---|---------------------|--|---|---|---------------------------------------|--------|
| 160 | Camera Interlinked 6 Zone Walk Through Metal Detector | DETECTOR-DF06CAMERA |  | Power Supply: 220V/110V Frequency:6.99-11khz Work Enviroment: -20℃ + 55℃ Power:<=30w Body size:2220*850*500mm Passage Width:2000*700*500mm Alarm Indication:Audio and Vibration at the same time. Display Panel:High quality digital tube with person number accessaccount 6 Zone detect sensibility class adjust RS485 Communication Port for Camera Inter-Linked 5.7Inch LCD Display Screen | / | More Photo ->Click | / |
| 161 | Luxury 6 Zone Digital Display Walk Through Metal Detector | DF06LUXURY |  | Power Supply: 220V/110V Frequency:6.99-11khz Work Enviroment: -20℃ + 55℃ Power:<=30w Body size:2210*835*500mm Passage Width:715mm Alarm Indication: Aarm Lightening ,Alarm vocie Display Panel:High quality digital tube with person number accessaccount 6 Zone detect sensibility class adjust | / | More Photo ->Click | / |

| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|--|---|--------------------------|---|---|---|---------------------------------------|--------|
| 12 ZONE Walk Through Metal Detector | | | | | | | |
| 162 | 12 Zone Walk Through Metal Detector | DF-12LUXURY |  | Power Supply: 220V/110V Frequency:6.99-11khz Work Enviroment: -20℃ + 55℃ Power:<=30w Body size:2210*835*500mm Passage Width:715mm Alarm Indication: Aarm Lightening ,Alarm vocie Display Panel:High quality digital tube with person number accessaccount 6 Zone detect sensibility class adjust | / | More Photo ->Click | / |
| 18 ZONE Walk Through Metal Detector | | | | | | | |
| 163 | Economical 18 Zone Walk Through Metal Detector | DETECTOR-18DF ECONOMICAL |  | 1. Detection procedure: level sensitivity adjustment, which can meet the needs of different occasions. 2. Personnel passing rate: more than 40 person-times per minute. 3. Power supply: 110-240V AC, 50/60Hz, power consumption: ≤ 18W. 4. Testing standard: one yuan coin 5. Display mode: 18-zone digital tube display | / | More Photo ->Click | / |
| 164 | 18 Zone Walk Through Metal Detector with led Lighting | DF-018LED |  | 1. Detection procedure: level sensitivity adjustment, which can meet the needs of different occasions. 2. Personnel passing rate: more than 40 person-times per minute. 3. Power supply: 110-240V AC, 50/60Hz, power consumption: ≤ 18W. 4. Testing standard: one yuan coin 5. Display mode: 18-zone 6-inch large LCD display 6. Working environment: -10℃ ~45℃, ≤95%RH. | / | More Photo ->Click | / |

| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|--|--|--------|--|--|---|--|--------|
| 33 ZONE Walk Through Metal Detector | | | | | | | |
| 165 | 33 Zone Walk Through Metal Detector | DF-033 |  | <ol style="list-style-type: none"> 1. Detection procedure: level sensitivity adjustment, which can meet the needs of different occasions. 2. Personnel passing rate: more than 40 person-times per minute. 3. Power supply: 110-240V AC, 50/60Hz, power consumption: ≤ 18W. 4. Testing standard: one yuan coin 5. Display mode: 33-zone 2.5-inch small LCD screen 6. Working environment: -10℃ ~45℃, ≤95%RH. | / | More Photo - >Click | / |
| 45 Zone Walk Through Metal Detector | | | | | | | |
| 166 | 45 Zone Walk Through Metal Detector 400 Level | DF-045 |  | <ol style="list-style-type: none"> 1. Detection procedure: level sensitivity adjustment, which can meet the needs of different occasions. 2. Personnel passing rate: more than 40 person-times per minute. 3. Power supply: 110-240V AC, 50/60Hz, power consumption: ≤ 18W. 4. Testing standard: one yuan coin 5. Display mode: 6-inch large LCD display in 45 areas 6. Working environment: -10℃ ~45℃, ≤95%RH. 7. Channel size: 2000 (height) * 700 (width) * 600 (depth) mm | / | More Photo - >Click | / |

| S/N | Name | Model | Picture | Technical Parameters | / | Link | Remark |
|----------------------------|----------------------------|-------------|---|---|---|--|--------|
| X Ray Baggage Scan Machine | | | | | | | |
| 167 | X Ray Baggage Scan Machine | X RAY-5030A |  | <p>Basic parameters Channel size: 505*305mm (width*height) Power belt speed: 0.22m/s Portal load: 100kg (uniform load) Passage: > 10mm steel plate Line split force:> 38AWG Space resolution: horizontal/vertical φ1.0mm</p> <p>X -ray source Control interface: Simulation interface Tube voltage: 80kV (adjustable) Tube current: 0.6 ~ 1.2ma (adjustable) Cooling method: sealing oil and cooling, industrial fan cooling Work Zhou Ming: 100 %, no top heat Protection function: over pressure, overcurrent, over -temperature protection Radiation safety index Dose rate: <0.5 μgy/h (5cm from the shell) Single dose: <1.0 μgy Safety: Safety of film, chip, and electronic products Radiation Protection: The passage and export of the channel use 0.5mmpb dual -layer Environmental protection lead curtain protection, the raw body uses 2 to 6mm lead plate protection to ensure that the peripheral radiation of the equipment meets national security standards</p> | / | More Photo - >Click | / |