

S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
-----	------	-------	---------	----------------------	---	------	--------

ShenZhen Sintronic

Technology Company Limited



Tim Wu
Sales Engineer










SINTRONICTECH
MAKE A DIFFERENCE


Address: No.3368, Pengrunda
Commercial Plaza Shenzhen
City, China.518000
Website: <https://sintronictech.com>
Email: tim@sintronictech.com
Mobile: +86-15813805304
China Leading Manufacturer
Access & Security System




scan this code using the WhatSapp camera to get my number


Access Control, Turnstile Gate, Security Guard
Parking Guidance, Parking Ticketing System



Manufacturer


S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
⑤							
	Parking System Manufacturing Department						
	Parking Ticketing System Price List						
	sintronicparking.com						
Car Plate Recognition Camera				RFID Parking Controller	RFID Parking Reader		
							
Page 3				Page 4	Page 4		
Barrier Boom Gate				Parking Ticket Box	Payment Machine		
							
Page 5-7				Page 8	Page 9		
Card Dispenser&Collector				Loop Detector			
							
Page 8				Page 9-10			





S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
Car Plate Recognition Camera							
203	Car plate recognition Camera	PS-01CAMERA		<ul style="list-style-type: none"> ◇ Ultra HD 4 million pixels (1440P); ◇ All-day vehicle capture rate is higher than 99.9%; ◇ All-day license plate recognition rate is higher than 95%; ◇ Support cloud control function for parameter configuration, video preview and remote upgrade; ◇ Adopt video compression technology H.264 for video encoding, and capture frames using JPEG encoding; . ◇ Support three detection methods: coil detection, video detection, coil detection + video detection ; ◇ Support OSD information overlay function, support video 1 picture overlay watermark; ◇ Support white list import and export function, can do fuzzy matching on white list; Support OEM For Global Country ◇ Support configuration file import backup ; ◇ Support manual key reset, you can restore the initial IP address, user name, password and restore the default factory configuration with one click ; ◇ Support cloud intercom ; 	/	More Photo ->Click	SDK,HTTP API for linkage to parking payment system



S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
RFID Parking Controller							
204	RFID Parking Ticketing Controller	PS-RFID TCP300		Working voltage: DC12V Working environment temperature: -25°C-60°C Relative humidity: =< 95% Card reader interface: WG26 Communication interface: RS485 Communication baud rate: 4800b/s Maximum communication distance: 1200 meters User Information: 6000 Offline Storage Record Capacity: 10000 Card type: optional IC, ID Card reading distance: 5 ~ 10cm (IC card)	/	More Photo ->Click	Parking management software in english version
Parking Ticketing Reader							
205	Entry Station RFID Reader	PS-ETYREADER		Entry Station RFID Parking Ticketing Reader IC Type 13.56Mhz	/	More Photo ->Click	IC
206	Exit Station RFID Reader	PS-EXTREADER		Exit Station RFID Parking Ticketing Reader IC Type 13.56Mhz	/	More Photo ->Click	IC


S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
Barrier Boom Gate							
207	AC Motor Stright Pole Boom Gate	BG-AC100		Barrier Boom Gate Octagonal Powder Coated Aluminum .50-60W Single phase asynchronous AC motor with over heat protection function .Brake rod landing time 0.2~6s .Work Enviroment -25~+60 Degree Relative humidity less than 95%& no condensation, Gate center to off-ground height 885mm Lifeleaf time:5 million times Size: 270*340*1000mm Thickness:1.5	/	More Photo ->Click	Gate Only Single Spring Without Pole (Bg-AC100)
							AC Motor Gate with 1-3 meters Pole Single Spring(Bg-AC103)
							High Power AC Motor Gate with 1-4meters Pole Single Spring(Bg-
							High Power AC Motor Gate with 1-5 meters Pole 2 Spring(Bg-AC105)
							Pure copper High Power AC Motor Gate with 1-6 meters Pole 2 Spring(Bg-AC106)

S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
208	Brushless Motor Stright Pole Boom Gate	BG-BRULSS 100		<p>Barrier Boom Gate Octagonal Powder Coated Aluminum .50-60W Single phase asynchronous Brushless motor with over heat protection function .Brake rod landing time 0.2~6s .Work Enviroment -25~+60 Degree Relative humidity less than 95%& no condensation, Gate center to off-ground height 885mm Lifeleaf time:5 million times Size: 270*340*1000mm Thickness:1.5</p>	/	More Photo - >Click	<p>Gate Only Single Spring Without Pole (BG- Brushless Motor Gate with 1-3 meters Pole 2 Spring(BG- Brushless Motor Gate with 1-4 meters Pole 2 Spring(BG-BRULSS104) Brushless Motor Gate with 1-5 meters Pole 2 Spring(BG-BRULSS105) High Power Brushless Motor Gate with 1-6 meters Pole 2 Spring(BG-BRULSS106)</p>
209	AC Motor Barrier Boom Gate	BG-AC200		<p>Barrier Boom Gate Octagonal Powder Coated Aluminum .50-60W Single phase asynchronous AC motor with over heat protection function .Brake rod landing time 2.5~6s .Work Enviroment -25~+60 Degree Relative humidity less than 95%& no condensation, Gate center to off-ground height 885mm Lifeleaf time:5 million times Size: 285*340*980 Thickness:2.0 Extra Thickness Steel Mounted Chip core motor and be stable running the 6 meter barrier rod</p>	/	None	<p>Gate Only (Frequency Changeable) (BG-AC200) Gate with 1-3 meters barrier AC motor (BG-AC203) Gate with 1-4 meters barrier BG-AC204 Gate with 1-5 meters Barrier BG-AC205 Gate with 1-6 meters Barrier BG-AC206</p>

S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
210	Brushless Motor Barrier Boom Gate	BG-BRULSS200		<p>Barrier Boom Gate Octagonal Powder Coated Aluminum .50-60W Single phase asynchronous Brushless motor with over heat protection function .Brake rod landing time 2.5~6s .Work Enviroment -25~+60 Degree Relative humidity less than 95%& no condensation, Gate center to off-ground height 885mm Lifeleaf time:5 million times Size: 285*340*980 Thickness:2.0 Extra Thickness Steel Mounted Chip core motor and be stable running the 6 meter barrier rod</p>	/	None	Brushless motor Gate with 1-3 meters barrier AC motor (BG-BRULSS203)
							High Power Brushless motor Gate with 1-4 meters barrier AC motor (BG-BRULSS204)
							High Power Brushless motor Gate with 1-5 meters barrier BG-BRULSS205
							High Power Brushless motor Gate with 1-6 meters Barrier BG-BRULSS206

S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
Parking Ticketing Box							
211	Ticket Box	TB -1325		Ticket Box for issue or return ic/id card Size:32*44*1325mm Available for card size of 85*54+-0.5mm with thickness of 0.2-2.4mm (adjustable)The default factory set up is 0.8mm	/	None	/
Parking Ticketing RFID Card Dispenser/Collector							
212	RFID card issue machine	CI-01		Available for card size of 85*54+-0.5mm with thickness of 0.2-2.4mm (adjustable)The default factory set up is 0.8mm	/	None	For use the functions of once the card been collected and the gate open Pls do 03 ov wire to GND,09 wire to boom gate open signal
213	RFID card collect machine	CC-01		Available for card size of 85*54+-0.5mm with thickness of 0.2-2.4mm (adjustable)The default factory set up is 0.8mm Support link to boom gate open once the card is been collected	/	None	 <ul style="list-style-type: none"> -1. 24V- -2. 24V+ 3. 0V (signal/ground) 4. card out signal 5. reset input -6. 0V (signal/ground) -7. ground sense signal input 8. Pre open input/ret/m input 9. gate open/card position output 10. less card output ..

S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
Parking Ticketing Payment Machine							
214	Auto Payment Machine	PM01		AUTOMATIC Payment machine with touch screen and have windows system support linkage to bank payment system between camera and boom gate	/	None	Card payment machine
Loop Sensor							
215	Ground Sense Vehicle Loop Detector	LOOP-01		Supply voltage:230V AC , 115V AC, 24V DC/AC, 12V DC/AC (Please the label on the detector for more information) Voltage tolerance AC:+10% / -15% Voltage tolerance: DC±15% Power Consumption:4.5VA Output relays:240V/5A Operating temperature:-20°C to +65°C Storage temperature:-40°C to		None	/

S/N	Name	Model	Picture	Technical Parameters	/	Link	Remark
216	Radar Anti Fall Loop Detector	RADAR-01		Transmit frequency:24.00-24.25 GHz Output power:10dBm Update rate:20ms Power consumption:1.5W Detection characteristics Detection distance:0.1~10meters Detection target:human, vehicle Distinguish following cars:0.6 meters Antenna characteristics Beam width/TX Horizontal in 22°, Elevation in 37° Hardware characteristics Supply voltage:6~24V DC Supply current:0.12A Operating temperature:-40~+85	/	None	/